

My America

by Deborah Edwards



NORTHCOTT
Cottons that feel like silk



MY AMERICA - WALL QUILT

FREE PATTERN • By Northcott Studio

Finished Size 43" x 61"

Northcott Canada
101 Courtland Avenue
Vaughan, Ontario L4K 3T5

Northcott USA
1050 Valley Brook Ave,
Lyndhurst, NJ 07071

www.northcott.com

My America Wall Quilt

Collection: MY AMERICA

Finished Size: 43" x 61"

WOF = width of fabric

All seams are sewn using a ¼" seam allowance

Fabric Requirements	Yardage	Cutting Instructions
Fabric A – Center 24025-90 or 24019-92 	2/3 yard	Trim to 23 ½" x 41 ½"
Fabric B – Inner Border & Binding  24017-24	3/4 yard	Cut 4 – 2 ½" x WOF strips Cut 6 – 2 ¼" x WOF strips; set aside for binding
Fabric C – Middle Border  24022-92	7/8 yard	Cut 4 – 6 ½" x WOF strips
Fabric D – Outer Border  24017-94	1/2 yd	Cut 5 – 2 ½" x WOF strips
Fabric E – Cornerstones  24018-12	1/4 yd	Cut 1 – 6 ½" x WOF strip <ul style="list-style-type: none"> • Sub-cut 4 – 6 ½" squares & 8 – 2 ½" squares
Backing  24024-90	2 yds	No cutting required

QUILT TOP ASSEMBLY:

1. Trim two Fabric B inner border strips to 41 ½" and sew one to each side of center panel. Press seams toward the center.
2. Trim two Fabric B inner border strips to 23 ½". Sew a 2 ½" x 2 ½" cornerstone to each end of both strips. Press seams toward the cornerstones. Then sew these strips to the top & bottom of the center panel, pressing the seams toward the center.
3. Join Fabric C border strips on the short edges. Repeat Steps 1 & 2 to attach the middle borders, measuring the length of the quilt through the center to determine what length to trim the side border strips and measuring the width of the quilt through the center to determine what length to trim the top & bottom border strips. Sew a 6 ½" x 6 ½" cornerstone to each end of the top & bottom border strips.
4. Join Fabric C border strips on the short edges, and add the outer borders in the same manner as above.
5. Layer quilt top with batting and backing. Quilt and bind as desired.
6. Join the binding strips end to end using diagonal seams and prepare binding. Bind using your favorite method.