



NORTHCOTT  
*Cottons that feel like silk*

# STONEHENGE OH CANADA! Our Home and Native Land



FREE PATTERN • **Our Native Land 60" x 72"** by Elaine Theriault of Northcott

**Northcott Canada**  
101 Courtland Avenue  
Vaughan, Ontario L4K 3T5


**Northcott USA**  
1099 Wall St. West, Suite 250  
Lyndhurst, NJ 07071

[www.northcott.com](http://www.northcott.com)

# Our Native Land

Finished Size: 60" by 72"

wof = width of fabric

| Fabric requirements   | Yard     | Cutting Instructions   |
|---|----------|--|
| <b>Fabric A:</b> Canada Flag Panel (#21615-11)                        | 1 panel  | Trim panel to 23 ½" by 43" (see NOTE below before cutting panels)  |
| <b>Fabric B:</b> Words on Beige (#20868-12)<br>Top and bottom borders | ½ yard   | Cut four (4) strips measuring 4 ¼" by wof  |
| <b>Fabric C:</b> Border print (#21617-11)<br>Top and bottom borders   | 1 ¼ yard | Fussy cut six (6) strips measuring approximately 3 ¼" wide by length of fabric<br>Careful cutting of the border will allow you to use the excess strips in another project<br> |
| <b>Fabric D:</b> Cream tonal (#21618-11)<br>Inner border              | ¾ yard   | Cut six (6) strips measuring 3 ½" by wof<br>• Join end to end using a diagonal seam for the inner border   |
| <b>Fabric E:</b> Symbols on red (#21616-24)<br>Outer border + binding | 1 ½ yard | Cut seven (7) strips measuring 6 ½" by wof<br>• Join end to end using a diagonal seam for the outer border<br>Cut seven (7) strips measuring 2 ½" by wof<br>• Join end to end using a diagonal seam for the binding  |
| <b>Backing</b>  | 3 ¾ yard | Pieced crosswise   |

Use ¼" Seam Allowance unless otherwise stated

## Top and bottom borders

- Using Fabric C, trim two (2) strips (3 ¼") to the same length as the width of your panel. Note the orientation of the border stripe. You may want them to be mirror images of each other (top and bottom) as indicated on the pattern front, or keep them all in the same orientation. Matching the center of the borders to the center of the panel, pin the ends and ease in either the panel or the border. This will help to keep the panel square if it's a bit wonky. Press away from the panel.
- Using Fabric B, trim two (2) strips (4 ¼") to the same length as the width of your panel. Using the technique described in Step 1, sew the borders to the top and bottom of the quilt center.
- Repeat Steps 1 and 2, alternating Fabrics B and C until you have 3 borders of Fabric C and two borders of Fabric B on both the top and bottom of the panel.

**Inner border:** Using Fabric D, cut two border strips to the length that corresponds to the length of your quilt. Measure the length through the center of the quilt. Using the technique outlined in Step 1 (top and bottom borders), sew a border strip to either side of the center section. Press towards the border. Cut two more border strips for the top and bottom that correspond to the width of your quilt and sew them to the top and bottom. Don't forget to match the center and the ends.

**Outer border:** Using Fabric E, cut two border strips to the length that corresponds to the length of your quilt. Sew a border strip to either side of the center section. Press towards the border. Cut two more border strips for the top and bottom that correspond to the width of your quilt and sew them to the top and bottom. Don't forget to match the center and the ends.

**NOTE:** It is best to NOT prewash preprinted fabrics such as panels and border prints. The fabric goes through many processes to be delivered to the consumer and there may be some size variations. If you're unable to cut the panels/border prints to the sizes mentioned above, cut the pieces to a size that works for your panels and adjust any other measurements accordingly.